Charger - 36V, 2A, DC 5.5*2.1 (5.5mm x 2.1mm) Connector & Wall Plug, Lithium, UL / ULC - PBCCHG3620DC5F1



Rating: Not Rated Yet Price

\$36.67

Ask a question about this product

Description

Charger 36V (Output 42.0V), 2A (2000mA), max amperage 3.0A at 50/60Hz, Standard Polarity with Smart Charge for use with Lithium batteries. Charger connector is an insulated DC 5.5*2.1 (5.5mm x 2.1mm) with standard wall plug for power input. UL/ULC certified, this UL/ULC is very important and required legal certification in USA and Canada, caution if price-shopping chargers online. Commonly used for a wide variety of kick scooters (such as the Segway G30 Max and Xiaomi lineups), electric scooters, mobility devices, electric ATVs/dirt bikes, ride-on cars, and countless other electric consumer products. And extremely common charger design for lithium 36V 2A products.

Be sure to use this charger only in the designated applications with corresponding power ratings and polarities. We do not warrant this product against misuse, all chargers are tested before leaving our facility.

- Voltage: 36V (Output 42.0V)
- Amperage: 2.0A (2000mA), Max Amperage 3.0A at 50/60Hz
- Polarity: Standard
- Connector: DC 5.5mm x 2.1mm (10.6mm long from tip to housing) & Wall Plug